



PERFORMANCE CHART FOR SINGLE PHASE QT SERIES 4" (100mm) SUBMERSIBLE PUMPSET

PUMP TYPE	MODEL	PIPE SIZE IN mm	DISCHARGE IN LITERS PER HOUR AT VARIOUS TOTAL HEADS IN FEET															
			25	50	75	100	125	150	175	200	225	250	275	300	325	350	375	400
0.5 HP 6 Stage	QT - 140	32	4000	3200	2600	1900	1300	750										
0.75 HP 13 Stage	QT - 250	32	3500	3300	2800	2500	2300	2000	1800	1400	1100	800						
1.0 HP 9 Stage	QT - 225	32	4100	3700	3000	2700	2500	1900	1500	1200	900							
1.0 HP 12 Stage	QT - 275	32	3850	3500	3300	3000	2750	2500	2100	1650	1400	1250	600					
1.0 HP 16 Stage	QT - 325	32	3500	3400	3300	3000	2800	2600	2300	2000	1800	1550	1250	1000	750			
1.5 HP 18 Stage	QT - 400	32	3700	3550	3400	3300	3150	2900	2750	2600	2400	2200	1950	1650	1350	1200	1000	750

PERFORMANCE CHART FOR THREE PHASE OM SERIES OPENWELL SUBMERSIBLE PUMPSET

PUMP TYPE	MODEL	PIPE SIZE IN mm	DISCHARGE IN LITERS PER MINUTES AT VARIOUS TOTAL HEADS IN FEET													
			10	20	30	40	50	60	70	80	90	100	110	120	140	
3.0 HP OPENWELL	OM - 350 HH	65 X 50			700	670	650	600	520	400	270	140				
5.0 HP OPENWELL	OM - 550 HH	65 X 50			680	675	670	660	650	640	630	620	570	550	480	
5.0 HP OPENWELL	OM - 565	75 X 65			1120	960	900	780	660	480	240					



Recommended Head Range